

TILLBEHÖR, FÖRSKRUVNINGAR ADE

Zoner:



Dragavlastning för ADE förskruvning

		II 2 G Ex II 2 D Ex e II / Ex d IIC IP68 10 bar -40°C...+100°C			LCIE 97 ATEX 6008 X		
Art. nr	Storlek	Dimensioner			Kabeldiameter		Material
		A	B	C	min. mm	max. mm	
CA810434	4	15	18	5	4	8,5	Förnicklad mässing
CA810534	5	19	22	5	8	12	
CA810634	6	24	27,5	6	8,5	16	
CA810734	7	30	33,5	8	12	21	
CA810834	8	41	45	8	16	27,5	
CA810934	9	48	52	9,5	21	34	
CA881034	10	55	59	9,5	27	41	
CA811134	11	64	69	12	33	48	
CA811234	12	72	78	12	40	56	
CA811334	13	85	92	16	47	65	
CA811434	14	95	103	16	54	74	
CA811534	15	110	118	18	63	83	
CA811634	16	120	128	18	72	93	



Jordningsbricka för ADE inre mantel

		II 2 G Ex II 2 D Ex e II / Ex d IIC IP68 10 bar -40°C...+100°C			LCIE 97 ATEX 6008 X	
Art. nr	Storlek	Dimensioner		Kabeldiameter		Material
		Ø A	h	min. mm	max. mm	
CA560630	6	13,9	4,0	7,5	11,0	Rostfritt
CA560730	7	18,3	4,8	10,5	15,0	
CA560830	8	23,8	5,7	14,0	20,0	
CA560930	9	31,0	7,2	18,0	26,5	
CA561030	10	38,3	8,2	24,0	32,5	
CA561130	11	45,3	8,8	30,0	39,5	
CA561230	12	52,8	9,5	36,0	46,5	
CA561330	13	60,8	10,1	43,0	54,5	
CA561430	14	71,0	11,4	50,0	61,0	
CA561530	15	60,5	12,6	57,0	72,5	
CA561630	16	89,5	12,6	67,0	81,2	

