

# HA11 USB

**USB handset  
with PTT button  
and cradle**

Article-No.:  
**6506-011-000-51**



## Product:

### Characteristics

- Dynamic microphone and ear capsule
- Large push-to-talk button
- Durable PEIGUM® spiral cable
- Cradle with locking mechanism for the handset with release button
- Solid plastic housing
- Hook switch mechanism
- Flame resistant plastic housing

### Options

- Loudspeaker in the cradle
- Cradle with force release buttons
- Customized HID coding
- Solid base plate

### Application Range

- Ideal for mobile and fixed installation radio systems

### Scope of Delivery

- Handset with PEIGUM® spiral cable, cradle and 2 m USB type A cable

## Technical Data:

### General

Housing:	Plastic PC-ABS, black
Dimensions:	Height 85 mm, Width 63 mm, Depth 213 mm
Weight:	380 g (34.5 oz)
Connection:	6-wire halogen free PEIGUM® spiral cable, 2 wire shielded, extension length max. 1.35 m, USB Type A cable
Operating and display elements:	1 PTT button (orange, freely programmable) release buttons, black
Storage temperature:	-30 °C to +70 °C (-22 °F to +158 °F)
Operation temperature:	-25 °C to +60 °C (-13 °F to +140 °F)

### Microphone

Operating voltage (DC):	5 V USB
Frequency range:	200 Hz to 6 kHz at -10 dB
Sensitivity (in LRGP):	1 mV/Pa (-60 dBV/Pa ± 3 dB)
Impedance:	200 Ω ± 20 % at 1 kHz
Directivity:	Omnidirectional

### Earpiece

Frequency range:	300 Hz to 4 kHz at -10 dB
Sensitivity:	26 dBPa/V ± 3 dB (IEC 3.2 Low-Leak Koppler)
Impedance:	300 Ω ± 20 % at 1 kHz
Maximum output:	10 mW