

# HA26 USB

**USB-Handset with  
PTT button and 2 buttons  
for controlling the volume**

Article-No.:  
**6506-008-000-51**



## Product:

### Characteristics

- Omnidirectional noise canceling electret microphone capsule
- Dynamic ear capsule
- Solid plastic housing
- 2 buttons for controlling the volume
- Automatic hook switch mechanism (A12 cradle only)
- Large push-to-talk button

### Options

- Customized HID coding

### Application Range

- Dispatcher and PA systems with increased ambient noise

### Accessories

- A10 cradle
- A12, A12/2, A12/L cradle

### Scope of Delivery

- Handset with USB-A cable 3 m

## Technical Data:

### General

Housing:	Plastic PC-ABS, black
Dimensions:	Height 41 mm, Width 58 mm, Depth 209 mm
Weight:	195 g (6.9 oz)
Connection:	halogen free cable, shielded, length 3 m, USB-A connector
Operating and display elements:	1 PTT button (orange), 2 buttons for controlling the volume (programmable)
Storage temperature:	-30 °C to +70 °C (-22 °F to +158 °F)
Operation temperature:	-25 °C to +60 °C (-13 °F to +140 °F)

### Microphone

Operating voltage (DC):	5 V USB
Frequency range:	200 Hz to 14 kHz at -10 dB
Sensitivity (in LRGP):	2 mV/Pa (-54 dBV/Pa ± 3 dB)
Impedance:	> 1 kΩ ± 20 % at 1 kHz/R <sub>L</sub> = 2 kΩ
Directivity:	Omnidirectional

### Earpiece

Frequency range:	300 Hz to 4 kHz at -10 dB
Sensitivity:	26 dBPa/V ± 3 dB
Impedance:	300 Ω ± 20 % at 1 kHz
Maximum output:	10 mW