

|                     |   |
|---------------------|---|
| <b>MODEL</b>        | <b>CMA260 0 DB</b>  |
| <b>ANTENNA TYPE</b> | <i>End-fed full 1/2 λ coaxial dipole antenna</i><br><br>* Full omni-directional radiation pattern<br>* DC-grounded (DC-short) - antistatic<br>* NO GROUNDPLANE NEEDED |
| <b>FREQUENCY</b>    | 2500 – 2690 MHz ( 4G/LTE )  |
| <b>IMPEDANCE</b>    | Nom. 50 Ω   |
| <b>POLARISATION</b> | Vertical  |
| <b>GAIN</b>         | 0 dBd ( 2,1 dBi )   |
| <b>BANDWIDTH</b>    | 100 MHz   |
| <b>VSWR</b>         | < 1.5   |
| <b>MAX. POWER</b>   | 40 Watt   |
| <b>COLOUR</b>       | White   |
| <b>LENGTH</b>       | Approx. 200 mm (conical)  |
| <b>WEIGHT</b>       | Approx. 0,230 kg  |
| <b>MOUNTING</b>     |   |
| <b>MATERIAL</b>     | PU-painted heavy duty Ø 18 mm glass-fibre tube and chrome plated brass<br><br>IP66 Classified   |
| <b>ORD.NO.</b>      | <b>771010</b>   |
| <b>TEMPERATURE</b>  | -40 - +70° C  |
| <b>CONNECTOR</b>    | N (f)   |
| <b>CABLE</b>        | No cable supplied   |

