

SALUKA-N-LED-OP-7500-258-G2-4K, IP66


Product type: 080007

Item number: 42097

IP66

 2/22


Linear luminaire designed for explosion hazardous areas for ATEX zone 2/22. Body made of painted steel sheet (RAL 9016) with EPDM gasket – alternatively stainless steel AISI304 or AISI316. Cover made of opal tempered safety glass. Fitted with high quality electronic components with high LED lifetime up to 100 000 h and an efficiency of 154 lm/W. Characterized by high splash and dust resistance IP66. Suitable for ambient temperatures from -20 °C to +60 °C (depending on luminaire variant). Silicone-free design. Designed to be mounted or suspended.


Dimensions

A x B x C	1605 mm x 192 mm x 90 mm
------------------	--------------------------

Net weight	8,05 kg
-------------------	---------

Specifications

Light technical data

Lighting fixture luminous flux	6661 lm +/-10%	Luminaire efficiency	151 lm/W
CRI	≥80	MacAdam	3
Beam angle	Very wide beam >80°	Colour temperature	4000 K

Electrical data

Power input	44 W	Rated voltage AC	220-240 V
Frequency	50/60 Hz	Rated voltage DC	220-240 V
Control method	ON/OFF luminaire	Insulation class	I
Number of luminaires per circuit breaker B10A	18	Number of luminaires per circuit breaker B16A	30
Number of luminaires per circuit breaker C10A	31	Number of luminaires per circuit breaker C16A	51
Momentum current	45 A		

Mechanical data

IP classification	IP66	IK classification	IK07
Warranty	5 years	Operating temperature	-20°C ≤ t ≤ 55°C

Certification

ATEX	FTZÚ 17 ATEX 0027X	EAC	EAES N RU E-CZ.PA01.B.01682/21
-------------	--------------------	------------	--------------------------------

Explosion protection ATEX

Ex ZONE	2/22	ATEX zone – gas	Ex II 3G Ex nR IIC T6 Gc
ATEX zone – dust	Ex II 3D Ex tc IIIC T80°C Dc		

Materials

Material of the body	painting steel sheet	Body colour	white RAL 9016
Cover material	OPG – frosted tempered safety glass		

Packaging**Barcode (EAN)**

8592040292214

Number of pieces per pallet

24 ks

Gross weight

8,96 kg

Accessories to order**EXTEND/SALUKA ceiling fixings set (2 pcs)**

Item number: **3583**
Product type: **051139**

**SALUKA flange Ø 50 mm (1 1/2"), AISI304**

Item number: **3589**
Product type: **051145**

**Stainless steel wall arm SALUKA AISI304 – 60 °C (1 pc)**

Item number: **3591**
Product type: **051147**


**Set of adjustable holders SALUKA (2 pcs)**

Item number: **28788**
Product type: **063754**

**SALUKA flange Ø 40 mm, AISI304**

Item number: **30316**
Product type: **064018**



Polar diagram

© 2026 All rights reserved. VYRTYCH a.s. does not warrant the accuracy or completeness of the information provided herein and is not responsible for any events that may occur as a result of unqualified reliance on this information. The information contained herein does not constitute a commercial offer and does not form part of a quotation or contract, unless confirmed by VYRTYCH a.s..