


CHARACTERISTICS

- IP65 rated waterproof luminaire with high impact resistance IK11+/80 J rated curved aluminium profile.
- Opalescent or clear diffuser with louvres or with optics
- For mounting as recessed wall luminaire or ceiling mounting
- Not apparent quick power connection
- Fine texture RAL 7016 anthracite grey ● finish

OPTIONS AVAILABLE ON REQUEST

- Motion detector adjustable via radio-control or smartphone
- Pack emergency version available
- High UV resistance or anti-graffiti coating
- Through wiring
- Side cable entry

 Vandal-proof tool available to order separately.
Code M4: 9800 0036
+

Code M5: 9800 0012



Radio-control for wireless control available to order separately.
Code: 9800 0010

SYSTEO E – Opalescent

220-240 V AC / 50/60 Hz



 direct 776

Length L (mm)	Power rating (W)	Luminaire light output (lm) 4000 K	Luminaire efficacy (lm/W)	Opalescent
1036	9	850	97	5808 14--
1036	14	1400	100	5802 14--
1036	26	2700	104	5803 14--
1316	19	1950	103	5804 14--
1316	37	3800	103	5805 14--

Durability: L80B10 / over 72 000 hours
L90B50 / 50 000 hours

Codification for 3000 K colour temperature:
replace the figure 4 by a 3.

for instance 4000K: 5802 14--
3000K: 5802 13--

Codification: replace the two dashes (--)
by the appropriate figures:
for instance 5802 14--

- 00 NO DETECTION
- 16 WITH PRO DETECTION + RADIO-CONTROL
- 21 DALI DIMMABLE + SWITCH DIMMING
- 44 WITH PRO DETECTION + RADIO-CONTROL + EXTINCTION WARNING
- 45 WITH PRO DETECTION + RADIO-CONTROL + STANDBY WARNING

SYSTEO E – Clear, with louvres

220-240 V AC / 50/60 Hz



direct 776

For ceiling mounting versions only

Length L (mm)	Power rating (W)	Luminaire light output (lm) 4000 K*	Luminaire efficacy (lm/W)	Clear
1036	11	1400	127	5836 14--
1036	16	2000	125	5837 14--
1316	16	2100	131	5838 14--
1316	26	3300	127	5839 14--

Durability: L80B10 / over 72 000 hours
L90B50 / 50 000 hours

* For precise figures, please refer to the technical data sheet.
UGR rating to be confirmed by a lighting study

**Codification for 3000 K
colour temperature:**

for instance 4000K: 5836 14--
3000K: 5836 13--

replace the figure 4 by a 3.

Codification: replace the two dashes (--)
by the appropriate figures:
for instance 5836 14--

00 NO DETECTION
21 DALI DIMMABLE + SWITCH DIMMING

SYSTEO E – Clear, with optics

220-240 V AC / 50/60 Hz



direct 776

For ceiling mounting versions only

Length L (mm)	Power rating (W)	Luminaire light output (lm) 4000 K*	Mounted clear 40° optics	Mounted clear 60° optics	Mounted clear 90° optics	Mounted clear batwing optics	Mounted clear wallwasher optics
1036	9	1050	5814 14--	5819 14--	5824 14--	5829 14--	5834 14--
1036	14	1750	5811 14--	5816 14--	5821 14--	5826 14--	5831 14--
1316	16	2450	5812 14--	5817 14--	5822 14--	5827 14--	5832 14--

Durability: L80B10 / over 72 000 hours
L90B50 / 50 000 hours

* For precise figures, please refer to the technical data sheet.
UGR rating to be confirmed by a lighting study

**Codification for 3000 K
colour temperature**

for instance 4000K: 5831 14--
3000K: 5831 13--

replace the figure 4 by a 3.

Codification: replace the two dashes (--)
by the appropriate figures:
for instance 5831 14--

00 NO DETECTION
16 WITH PRO DETECTION + RADIO-CONTROL
21 DALI DIMMABLE + SWITCH DIMMING
44 WITH PRO DETECTION + RADIO-CONTROL + EXTINCTION WARNING
45 WITH PRO DETECTION + RADIO-CONTROL + STANDBY WARNING

