

IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres for rules and details of the IECEx Scheme visit www.iecex.com						
Certificate No.:	IECEx BKI 07.0005	Page 1 of 3	Certificate history:			
Status:	Current	Issue No: 3	lssue 2 (2013-11-12) Issue 1 (2011-09-19)			
Date of Issue:	2018-11-22		Issue 0 (2007-03-06)			
Applicant:	Cooper Crouse-Hinds GmbH previously CEAG Sicherheitstechnik GmbH Neuer Weg Nord 49 D-69412 Eberbach, Germany Germany					
Equipment:	Load, master, motor and safety switch					
Optional accessory:	Type GHG 26R					
Type of Protection:	General requirements, Flameproof enclosure, Increased safety, Dust explosion protection					
Marking:	Ex de IIC T6 -55 °C ≤ Tamb ≤ +45 °C Ex tD A21 IP66 T53°C					
Approved for issue on behalf of the IECEx Certification Body:		Edit Molnár				
Position:		Head of the Certification Body				
Signature: (for printed version)						
Date:						
2. This certificate is not	chedule may only be reproduced in full. transferable and remains the property of the issuing body. enticity of this certificate may be verified by visiting www.ie					
Certificate issued	by:		Aspiztos Beren R			
Testing Station 1 H 1037 BUDAPE MIKOVINY S.u. 2 Hungary			Vizsgáló Allomása			



IECEx Certificate of Conformity

Certificate No.:	IECEx BKI 07.0005	Page 2 of 3		
Date of issue:	2018-11-22	Issue No: 3		
Manufacturer:	Cooper Crouse-Hinds GmbH previously CEAG Sicherheitstechnik GmbH Neuer Weg Nord 49 D-69412 Eberbach, Germany Germany			
Additional manufacturing locations:				
This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended				
STANDARDS : The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards				
IEC 60079-0:2004 Edition:4.0	Electrical apparatus for explosive gas atmospheres - Part 0: Gene	eral requirements		
IEC 60079-1:2001 Edition:4	Electrical apparatus for explosive gas atmospheres - Part 1: Flam	eproof enclosures 'd'		
IEC 60079-7:2001 Edition:3	Electrical apparatus for explosive gas atmospheres - Part 7: Incre	ased safety 'e'		
IEC 61241-0:2004 Edition:1	Electrical apparatus for use in the presence of combustible dust -	Part 0: General requirements		
IEC 61241-1:2004 Edition:1	Electrical apparatus for use in the presence of combustible dust -	Part 1: Protection by enclosures "tD"		
	This Certificate does not indicate compliance with safety and other than those expressly included in the Standar			

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

HU/BKI/ExTR07.0004/00

Quality Assessment Report:

DE/BVS/QAR11.0009/08



IECEx Certificate of Conformity

Certificate No .:

IECEx BKI 07.0005

Date of issue:

2018-11-22

Page 3 of 3

Issue No: 3

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

See details in Addendum to IECEx BKI 07.0005 Certificate of Conformity

SPECIFIC CONDITIONS OF USE: NO Issue 3

deleting the manufacturing location S.C. COOPER INDUSTRIES ROMANIA S.R.L

Issue 2 Adding new manufacturing location: S.C. COOPER INDUSTRIES ROMANIA S.R.L ARAD, Zona Industrial NV, str III, no 12 ROMANIA

The IECEx QAR of the new manufacturing location: DE/BVS/QAR11.0006/02

Issue 1 new QAR: DE/BVS/QAR11.0009/00

Annex:

Addendum to IECEx BKI 07.0005.pdf



ADDENDUM TO IECEX CERTIFICATE OF CONFORMITY IECEX BKI 07.0005

Page 1 of 2

1. Description

The load, master, motor and safety switch of type GHG 26.R... is composed of one or two enclosures made of plastics, sheet steel or Cu-Ni alloy of the type of protection increased safety "e" with incorporated – separately certified – built-in switch components and, if and when required, one or two auxiliary switches of the type of protection flameproof enclosure "d" and, depending on the enclosure size, with incorporated – separately certified – measuring instruments, pushbuttons, indicating lamps and terminals. Via an additional operating knob, a leading converter can be controlled in front of the cut-off point proper. Cable entries, for which a separate certificate has been issued, are used for external connection.

The load interrupter, master, motor protection and safety switch type GHG 26. R may now also be used in areas where potentially explosive atmospheres with dust/air mixtures may occasionally occur.

The composition of the symbol specifying the type of protection depends on the types of protection of the components used.

2. Type assortment

GHG 26.R.... Legend of the signs from left to right

1._, 2._, 3._ 4._, 5._ 6._

7._, 8._ 9._, 10._ Code for manufacturer Apparatus (switch) Rated current 5 = 125 A6 = 180 AEnclosure design Number of poles No influence on protection

3. General parameters

11._, 12._, 13._, 14._, 15._

Technical data

Built-in switch component GHG 26.R....

 $\begin{array}{c} \mbox{Utilization category AC 1} \\ \mbox{Rated voltage } U_e \hdots \hd$

Utilization category AC 1 Rated voltage U_e up to 690 V Rated current I_e max. 20 A

Utilization category AC 3 Rated voltage U_e up to 400 V 500 V 690 V Rated current I_e max. 20 A 16 A 10 A

Utilization category DC 11 Rated voltage U_e up to 24 V 110 V 230 V Rated current I_e max. 6 A 0,6 A 0,4 A L/R 60 ms 30 ms 20 ms

Rated cross-section max. 2,5 mm² (finely stranded) or 4 mm² (single core)



ADDENDUM TO IECEX CERTIFICATE OF CONFORMITY IECEX BKI 07.0005

Page 2 of 2

In accordance with the relevant provisions, rated values other than those stated above are permissible if the making and breaking capacity is complied with; they must be specified by the manufacturer, dependent on the mode of operation, utilization category, etc.

4. Ambient temperature

Ambient temperature up to -55 °C \leq Tamb \leq +45 °C

5. Ingress protection IP66 by IEC 60529

Conditions of Certification: No

No. 4210	(9 sheets)	1999.10.07			
No. 4210	(3 sheets)	1999.10.07			
	. ,				
GHG 260 7211 P0002 D/EF(F)	(8 sheets)	2000.11.15			
GHG 260 7007 P0001 D/EF(F)	(6 sheets)	2000.11.15			
GHG 265-1-4284		1999.11.08			
265-1-4286		1999.11.08			
265-1-4287		1999.11.08			
266-1-4285		1999.11.08			
266-1-4288		1999.11.08			
266-4-4283		1999.11.08			
Nr. 4210	(1 sheet)	2001.04.10			
BVS PP01.2024 EG.		2001.03.19			
VB-IE1-ExS-86.06		1986.05.28			
IEC Ex Certificate of ConformityIEC Ex BKI 05.0011U					
IEC Ex Certificate of Conformity IEC Ex BKI 05.0015U					
VB-IE1-EXS-85.09		1985.06.11			
	No. 4210 GHG 260 7211 P0002 D/EF(F) GHG 260 7007 P0001 D/EF(F) GHG 265-1-4284 265-1-4286 265-1-4287 266-1-4285 266-1-4288 266-4-4283 Nr. 4210 BVS PP01.2024 EG. VB-IE1-ExS-86.06 yIEC Ex BKI 05.0011U yIEC Ex BKI 05.0015U	No. 4210 (3 sheets) GHG 260 7211 P0002 D/EF(F) (8 sheets) GHG 260 7007 P0001 D/EF(F) (6 sheets) GHG 265-1-4284 265-1-4286 265-1-4287 266-1-4285 266-1-4288 266-4-4283 Nr. 4210 (1 sheet) BVS PP01.2024 EG. VB-IE1-ExS-86.06 yIEC Ex BKI 05.0011U yIEC Ex BKI 05.0015U			