

i.safe MOBILE





IS330.1

Rugged, safe and built for any challenge!

The Zone 1/21, CL I/DIV 1 key-operated phone of the new generation:

Android™ 10, Bluetooth® 5, huge internal memory 64 GB, multifunctional ISM interface, amplified loudspeaker, SOS key, programmable Key-with optional PTT feature

) i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Bluetooth* is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi* is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners. © 2021 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1027MD011REV09_EN_06.2021



i.safe MOBILE

TECHNICAL FEATURES



ATEX approval: EX-Zone 1/21 (a) II 2G Ex ib IIC T4 Gb Db IP6X



EAC approval: 1Ex ib IIC T4 Gb X Ex ib IIIC T135°C Dc X



Android™ 10



Bluetooth® 5



External memory microSD up to 128 GB



Dual nano-SIM



IECEx approval: EX-Zone 1/21 Ex ib IIC T4 Gb Ex ib IIIC T135°C Db IP6X



2,4 GHz + 5 GHz: IEEE 802.11a/b/g/n/ac/e/k/r/h with max. 8 connections hotspot



Size: 152,8 x 62 x 26,7, weight: 318 g



2 cameras: 13 MP AF rear camera and 5 MP FF front camera



Near Field Communication



Universal, lateral ISM interface



NEC500 approval: Class I, II, III Division 1 Groups ABCDEFG, T4 Intrinsically Safe



GSM 850/900/1800/ 1900 MHz WCDMA: UMTS B1/2/4/5/8 LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/ 26/28A/28B/29/30/66 LTE-TDD: B38/B39/B40/B41 TD-SCDMA: B34/B39



Qualcomm Snapdragon SDM660 Octa-Core (Krvo Gold-Ouad cores 2,2 GHz; Kryo Silver-Quad cores 1.8 GHz). 4 GB RAM. 64 GB internal memory



SOS key Loneworker protection LWP ready (third party application required, based on country specific regulations)

FURTHER FEATURES



Waterproof: 1 hour up to 2 m, impervious to dust and microparticles



Operation range from -20 °C to 60 °C



Drop-protection, tested against: vibrations, shock and extreme temperatures.



2.6" Gorilla Glass® 3. generation, resolution 320 x 432 pixel



Usable with gloves



Amplified loudspeaker



4050 (typ. 4200) mAh Battery, replaceable, 3.8 V: 14.98 Wh



GPS, A-GPS, Glonass, Beidou, Galileo



G-sensor, gyroscope, gravity, ambient light, magnetic- and proximity

SET CONTENT

Mobile Phone, Battery, i.safe PROTECTOR 2.0 Type C USB Cable, Adapter, Screwdriver, Quick Start Manual and Safety Instructions

WWW.MALUX.SE ΕN