



**ZONE 2/22
CL I / DIV 2**

IS330.2

Rugged, safe and built for any challenge!

The Zone 2/22, CL I/DIV 2 key-operated phone of the new generation:

Android™ 10, Bluetooth® 5, huge internal memory 64 GB, multifunctional ISM interface, amplified loudspeaker, SOS key, MCPTT ready



➤ i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Bluetooth® is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi® is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners. © 2021 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1043MD01REV06_EN_05.2021

TECHNICAL FEATURES



ATEX approval:
EX-Zone 2/22
Ⓢ II 3G Ex ic IIC T4 Gc IP64
Ⓢ II 3D Ex ic IIIC T135°C
Dc IP64



IECEx approval:
EX-Zone 2/22
Ex ic IIC T4 Gc IP64
Ex ic IIIC T135°C Dc IP64



NEC approval:
Class I Div. 2 Groups
A, B, C, D, T4
Class II Div. 2 Groups
F, G, 135°C
Class III Div. 2



Android™ 10



2,4 GHz + 5 GHz: IEEE
802.11a/b/g/n/ac/e/k/r/h
with max. 8 connections
hotspot



GSM 850/900/1800/
1900 MHz
WCDMA: UMTS B1/2/4/5/8
LTE-FDD: B1/2/3/4/5/7/8/12
with MFBI B13/14/17/20/25/
26/28A/28B/29/30/66
LTE-TDD: B38/B39/B40/B41
TD-SCDMA: B34/B39



Bluetooth® 5



Size: 152,8 x 62 x 26,7,
weight: 318 g



External memory
microSD up to 128 GB



2 cameras: 13 MP AF
rear camera and 5 MP FF
front camera



Qualcomm Snapdragon
SDM660 Octa-Core
(Kryo Gold-Quad cores
2,2 GHz; Kryo Silver-Quad
cores 1,8 GHz),
4 GB RAM,
64 GB internal memory



Dual nano-SIM



Near Field
Communication



SOS key
Loneworker protection
LWP ready (third party
application required,
based on country specific
regulations)



Universal, lateral
ISM interface

FURTHER FEATURES



Waterproof: 1 hour
up to 2 m, impervious to
dust and microparticles



Operation range from
-20 °C to 60 °C



Drop-protection,
tested against: vibrations,
shock and extreme
temperatures.



2,6" Gorilla Glass®
3. generation,
resolution 320 x 432 pixel



Usable with gloves



Amplified loudspeaker



4050 (typ. 4200) mAh
Battery, replaceable,
3,8 V; 14,98 Wh



GPS, A-GPS, Glonass,
Beidou, Galileo



G-sensor, gyroscope,
gravity, ambient light,
magnetic- and proximity
sensor

SET CONTENT

Mobile Phone, Battery, Type C USB Cable, Adapter, Quick Start Manual and Safety Instructions