

## TRAINTALK™ OVK6

GSM-R 2W TrainTalk™ OVK6  
The new updated OVK model.

A complete unit that easily and quickly replaces Sagem OVK3 and Malux OVK4 and OVK5 solution that is already in many trains.

The phone is purchased separately depending on needs.

Electrical Specifications	
Powersupply	12 - 32 V DC
Antenna connector	TNC-Female or customer request
Integrated	Speaker, Hand set, Goose Neck mic.
Compliant with	
Fire	EN 45545-2:2020+A1:2023
EMC and ESD	EN 50121-4-2:2017 EN 50121-4:A1:2019 EN 61000-6-4:2019
Vibration and Shock	EN 61373:2010 / EN 50155:2021
Temperature operating	-25°C – +85°C
Temperature in stock	-40°C – +85°C
Mechanical Specifications	
Dimensions	200 x 200 x 150 mm
Weight	5kg
Material enclosure	Plastic/Metal
Product accessories	
PN. 780041	Swivel Mount for cradle
P.N 780374	Short Goose Neck Microphone 240mm

PN.	Description
785656	OVK6 SED OPH-810R 900MHz without cabin activation
785655	OVK6 SED OPH-810R 900 MHz with cabin activation

### Cabin Activation

#### No Cab activation

Power to the TrainTalk (Pin 1 and 2)	= Charging of the phone
No power to the TrainTalk (Pin 1 and 2)	= No charging of the phone.
When power is on pin 1 and 2, you will have charging of the phone and the handsfree will be activated.	

#### Cab activation

Power to the TrainTalk (Pin 1 and 2)	= Charging of the phone.
Cabin activated (Pin 3 and 4 connected)	= Handsfree activated.
Cabin de-activated (Pin 3 and 4 not connected)	= Handsfree de-activated.
No power to the TrainTalk (Pin 1 and 2)	= No chargin of the phone.

