


Exit Cube 33022 LED CG-S

Emergency Sign Luminaire




Exit Cube 33022 LED CG-S

- Exit sign cube with LED Technology for large, wide areas, e.g. warehouses or retail areas
- Robust design with impact-resistance of IK07
- Low operating costs via low connected load
- Minimum maintenance effort via use of LEDs with high service life (up to 50,000 hours)
- Modular design of the polycarbonate cube enables simple and safe mounting by just sliding cube onto installed luminaire
- Easy and flexible mounting options with space to land cables- Ceiling, wall, cable and chain.
- Optimal perceptibility due to high luminance of the white contrasting colour ($> 500 \text{ cd/m}^2$) acc. DIN 4844-1 / ISO 3864-1 (for bright environments) and high uniformity $L_{\min}/L_{\max} > 0,4$ (in mains operation)
- Reduced operating costs on account of especially low power consumption
- Shorten inspection effort due to CEWA GUARD technology
- Automatic function monitoring for up to 20 luminaires per circuit
- Reduced installation cost with STAR Technology
- Freely programmable mixed operation, allowing the switching of luminaire modes within one circuit

Exit Cube 33022 LED CG-S



Dimensions in mm



Wall bracket



Chain mounting kit



Cable mounting kit



Replacement escape sign cube



Viewing Distance	20 m
Luminous flux Φ_E/Φ_N at the end of rated operating time	100 %
Housing material	Cube: polycarbonate; enclosure: coated steel sheet
Housing colour	White RAL 9010
Weight	Luminaire 1.1 kg Cube: 0.6 kg
Type of mounting	Ceiling or wall mounting (bracket required)
Connection terminals	Loop terminals 3 x 2.5 mm ²
Connection voltage	220 - 240 V AC, 50/60 Hz 176 - 275 V DC
Current consumption with battery operating	25 mA
Power consumption mains operation (apparent power / effective power)	9.5 VA / 5.9 W
Permissible temperature range	-20 °C to +40 °C
Light source	HighPower LEDs 4 x 1 W

Ordering details

Scope of supply

Exit Cube 33022 LED CG-S: Enclosure and exit sign cube, for 20 m viewing distance with LED Supply and CG-S Technology (20 addresses), silkscreened pictograms (arrow left, right, down) acc. to ISO 7010



Order No

40071353421

Ordering details accessories

Scope of supply

Wall bracket incl. attachments

Order No

40071353444

Chain mounting kit with 4 eyelets (chain not included)

40071353457

Cable mounting kit with 4 fasteners and cables, adjustable hanging height (max 1.5 m)

40071353443

Replacement escape sign cube (20 m viewing distance) silkscreened pictograms (arrow left, right, down) acc. to ISO 7010



40071354450