

GL2 Compact

5068

Optic: 5068








Protector: Flat, Glass Extra Clear, Smooth

Source: 32 LEDs

Matrix: 33628S



Characteristics

						
468	193	137	5,3	IP 66	IK 08	I
Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Tightness level*	Impact resistance*	Electrical class*

* According to IEC-EN60598 and IEC-EN62262

Features

Compact, powerful and efficient LED solution to cover the lighting the entrance, threshold and interior zones

- Maximised savings in energy and maintenance costs
- LensoFlex®2 offering high performance photometry, comfort and safety
- Flexible solution: extruded aluminium profile to adjust number of LEDs for tunnel requirements
- High tightness level and excellent heat dissipation for long lasting performance
- High level of protection against corrosion, impact and vibrations
- Various inclination possibilities on-site for optimal photometry
- Control system can be integrated into the backbone system

Information for 1000 lm matrix

Efficacy (%): 81,9	G Class (EN 13201-2): G2
ULOR (%): 0,0	Imax (cd): 244
DLOR (%): 81,9	Aperture 0-180°: 79 - 79
UWLR (%): 0,0	Aperture 90-270°: 61 - 61
	I 70-80-90-95 (cd): 241 - 103 - X - X

US standard

IES Type: III - Medium
Nema type: 7x7

Photometrical characteristics

LED count	Colour code	Colour name	CCT (K)	CRI	Current (mA)	Luminaire power (W)	Luminaire output flux (lm)	Luminaire efficacy (lm/W)	Peak (cd)	BUG Rating
Ambient temp = 25°										
32	NW	Neutral White	4250	70	350	36	3746	104	914	B2 U0 G2
32	NW	Neutral White	4250	70	500	51	5019	98	1225	B2 U0 G2
32	NW	Neutral White	4250	70	700	71	6368	90	1554	B3 U0 G3

Summary

CONCEPT

Family of 5 tunnel LED luminaires:

Applications:

Dimensions (mm):

- Width: 193,00
- Height: 137,00
- Length: 468,00

Weight (kg): 5,30

Recommended height installation: between 4,00 and 6,00m

A flexible solution to cover all the lighting requirements of different tunnel areas

High tightness level IP66 and excellent heat dissipation (the driver and LED engine are in separate compartments) for long lasting performance

HOUSING & FINISH

- Housing in extruded aluminium protected by electrolytic oxidation (class 15)
- End caps: high-pressure, die-cast aluminium, polyester powder coated
- Screws in stainless steel
- Protector: thermally hardened glass
- A door on one of the end caps provides access to the electronic compartment.

Quick connectors allow easy removal of the gear tray.

- Colour: RAL 7040 light grey
- Luminaire Cd.S(drag): N/A
- Tightness - driver & optical: IP66
- Shock resistance: IK08

INSTALLATION

- Flexible installation, GL2 Compact can be fitted to all types of mounting systems
- Standard adjustable bracket: a tiltable bracket from -60° to +60° allows a precise on-site setting
- This versatile fixation is designed to be used in all kind of configuration: central line, corners or wall mounting

OPTICAL UNIT

- IP66 optical unit
- Protected against lens degradation with a 5mm thick extra clear hardened glass
- Flatbed PCB with acrylic lens overlay principle
- Various photometric distributions for lighting town, motorway and railway tunnels, underpasses
- The photometry can be symmetrical or asymmetrical for excellent luminance uniformity
- CRI > 70
- ULR: 0%

LED lumen depreciation

- Lifetime residual flux @ Tq=25°C @ 100.000 hrs : 350mA&500mA:90% ; 700mA:80%

ELECTRICAL

- Class I
- Input voltage: 120-277V - 50-60Hz
- Power factor > 90% at full load
- 10kV surge protection


STANDARDS & CERTIFICATIONS

- CE
- ENEC
- LM79-80
- ETL
- ROHS
- All measurements in ISO17025 accredited laboratory


OPTIONS

- Other RAL or AKZO colours
- Other fixations
- CW or WW LEDs
- Control system: Bi-Power, Dimming 1 -10V, DALI, Custom Program

Polar/Cartesian diagram



Isolux



K-Curve

