

# GL2 Compact

5068

Optic: 5068




Protector: Flat, Glass Extra Clear, Smooth

Source: 64 LEDs

Matrix: 336282



## Characteristics

						
718	193	137	7,5	IP 66	IK 08	I
Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Tightness level*	Impact resistance*	Electrical class*

\* According to IEC-EN60598 and IEC-EN62262

## Features

Compact, powerful and efficient LED solution to cover the lighting the entrance, threshold and interior zones

- Maximised savings in energy and maintenance costs
- LensoFlex®2 offering high performance photometry, comfort and safety
- Flexible solution: extruded aluminium profile to adjust number of LEDs for tunnel requirements
- High tightness level and excellent heat dissipation for long lasting performance
- High level of protection against corrosion, impact and vibrations
- Various inclination possibilities on-site for optimal photometry
- Control system can be integrated into the backbone system

## Types of application

- Tunnels

## Information for 1000 lm matrix

Efficacy (%): 81,9

ULOR (%): 0,0

DLOR (%): 81,9

UWLR (%): 0,0

G Class (EN 13201-2): G2

Imax (cd): 277

Aperture 0-180°: 79 - 79

Aperture 90-270°: 59 - 49

I 70-80-90-95 (cd): 276 - 128 - X - X

## US standard

IES Type: III - Medium

Nema type: 7x7

## Photometrical characteristics

LED count	Colour code	Colour name	CCT (K)	CRI	Current (mA)	Luminaire power (W)	Luminaire output flux (lm)	Luminaire efficacy (lm/W)	Peak (cd)	BUG Rating
Ambient temp = 25°										
64	NW	Neutral White	4250	70	350	70	7495	107	2076	B2 U0 G2
64	NW	Neutral White	4250	70	500	99	10043	101	2782	B3 U0 G3
64	NW	Neutral White	4250	70	700	139	12741	92	3529	B3 U0 G3

## Summary

### CONCEPT

Family of 5 tunnel LED luminaires:

Applications: Tunnels

Dimensions (mm):

- Width: 193,00
- Height: 137,00
- Length: 718,00

Weight (kg): 7,50

Recommended height installation: between 4,00 and 6,00m

A flexible solution to cover all the lighting requirements of different tunnel areas

High tightness level IP66 and excellent heat dissipation (the driver and LED engine are in separate compartments) for long lasting performance

### HOUSING & FINISH

- Housing in extruded aluminium protected by electrolytic oxidation (class 15)
- End caps: high-pressure, die-cast aluminium, polyester powder coated
- Screws in stainless steel
- Protector: thermally hardened glass
- A door on one of the end caps provides access to the electronic compartment.

Quick connectors allow easy removal of the gear tray.

- Colour: RAL 7040 light grey
- Luminaire Cd.S(drag): N/A
- Tightness - driver & optical: IP66
- Shock resistance: IK08

### INSTALLATION

- Flexible installation, GL2 Compact can be fitted to all types of mounting systems
- Standard adjustable bracket: a tiltable bracket from -60° to +60° allows a precise on-site setting
- This versatile fixation is designed to be used in all kind of configuration: central line, corners or wall mounting

### OPTICAL UNIT

- IP66 optical unit
- Protected against lens degradation with a 5mm thick extra clear hardened glass
- Flatbed PCB with acrylic lens overlay principle
- Various photometric distributions for lighting town, motorway and railway tunnels, underpasses
- The photometry can be symmetrical or asymmetrical for excellent luminance uniformity
- CRI > 70
- ULR: 0%

### LED lumen depreciation

- Lifetime residual flux @ Tq=25°C @ 100.000 hrs : 350mA&500mA:90% ; 700mA:80%

### ELECTRICAL

- Class I
- Input voltage: 120-277V - 50-60Hz
- Power factor > 90% at full load
- 10kV surge protection


### STANDARDS & CERTIFICATIONS

- CE
- ENEC
- LM79-80
- ETL
- ROHS
- All measurements in ISO17025 accredited laboratory


### OPTIONS

- Other RAL or AKZO colours
- Other fixations
- CW or WW LEDs
- Control system: Bi-Power, Dimming 1 -10V, DALI, Custom Program

### Polar/Cartesian diagram



### Isolux



### K-Curve

